

3M™ Extreme Sealing Tape 4411 & 4412 Series

Extremely
Fast
Clean
Easy

From trailer, bus and rail car roof seams to metal enclosures, a sure winner over traditional sealants

3M™ Extreme Sealing Tape – instant sealing that rolls on fast and looks good

- Sticks on contact to many metals and plastics without drying time, dripping, oozing and clean-up
- No sticky adhesive mess
- Conforms over contours, edges, rivets and screw heads for a water tight seal
- Clean – no mess, no caulking guns and no empty cartridges
- Paintable to colour-blend with the adjoining surfaces
- Neat and precise looking to improve aesthetics

Over time even more extreme advantages become obvious

- Holds securely through sun, rain, snow, temperature extremes and abrasion
- Stays flexible to compensate for vibration and thermal expansion/contraction
- No cracking and crumbling

- Trailer and RV roofs
- Metal enclosures
- Awnings
- Caravan roofs
- Metal buildings
- Vent stacks and vent windows
- Gutters and downspouts
- Skylights
- Outdoor sign/display
- Leak patching and temporary repairs
- Almost anywhere sealants are used



3M™ Extreme Sealing Tape – rolls on fast, seals instantly and stays tight



Simply clean with a solution of 50:50 water and isopropyl alcohol and wipe dry.



Sticks on contact exactly where you roll it on. No drips and oozing. No waiting.



Roll down with a soft roller to conform over contours, seam edges, rivets or screw heads.




Peel off the protective release liner.

The winner over liquid sealants

3M™ Extreme Sealing Tapes seal seams with roll-on speed for increased productivity and permanent strength for long term confidence with assured and consistent sealing results.

The winner over other tapes

With high shear and peel strengths, 3M™ Extreme Sealing Tapes seal with confidence through heat, cold and weather without cracking or edge lifting and with proven outdoor durability.




Product Information

Product/Colour	Comments	Backing/Adhesive	Tape Thickness (mm)	Tensile Strength (N/cm)	90° Peel Strength (N/cm)				Width (mm)
					Aluminium	Steel	PVC	ABS	
4411G	Colour matched to metal	Ionomer film/ Pressure sensitive acrylic	1.0	220	26.7	27.3	25.8	27.1	50
4411N	Low profile or economical applications				25.6	26.4	27.2	28.1	
4412G	Colour matched to metal		2.0	110	30.8	30.7	32.1	32.2	25, 50, 75, 100
4412N	Most robust sealing performance				31.7	31.5	33.5	32.3	

N=Neutral/Translucent G=Grey **Note:** This technical information and data should be considered representative or typical only and should not be used for specification purposes.

Now also available . . .
2 Metre Emergency Repair Tape



**3M Australia Pty Ltd
Industrial Adhesives &
Tapes Division**
Bldg A, 1 Rivett Road
North Ryde NSW 2113
Australia
Phone 136 136
www.3m.com.au

**3M New Zealand Ltd
Industrial Adhesives &
Tapes Division**
94 Apollo Drive, Albany
Auckland, New Zealand
Phone: 0800 474 787
Fax: 0800 362 880
Email: 3mznzib1@mmm.com

3M is a trademark of 3M Company.

Printed in Australia.

© 3M 2012. All rights reserved.