

# PRODUCT DATA SHEET



## 592 POLYESTER MASKING TAPE

High temperature masking and splicing.

### Product Features and Applications:

- \* General purpose high temperature splicing tape.
- \* High temperature masking tape for powder coating.
- \* Suitable for use as a flash breaker in the aerospace industry.
- \* Masking printed circuit boards during wave soldering.
- \* High temperature photo splicing tape for automatic developing machines.
- \* Ideal for tabbing and holding in thermal transfer sublimation.

### Product Specifications:

* Backing:	Polyester
* Adhesive:	Silicone
* Total thickness:	0.10mm
* Maximum width:	960mm
* Liner:	Self wound
* Colour:	Green
* Tensile strength:	18.0kg per 25mm
* Adhesion to steel:	1.0kg per 25mm
* Temperature resistance:	204 deg. C
* Elongation:	70%

**NOTE: When applying pressure sensitive adhesives, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.

MP110105

Freecall:1800 008 590  
Facsimile:(02)4732 1488  
[www.adept-industrial.com.au](http://www.adept-industrial.com.au)  
[sales@adept-industrial.com.au](mailto:sales@adept-industrial.com.au)

