

3M™ All Weather Flashing Tape 8067



Split liner for easier, faster installation.

No primers, no staples, no bleeding. No nonsense!

3M™ All Weather Flashing Tape 8067 is engineered to increase productivity while solving the most critical flashing problems. Unique acrylic pressure sensitive adhesive sticks and stays stuck to seal around windows, doors and other openings as well as for sealing joints in rigid air barriers. To prevent moisture intrusion, the thin backing construction effectively conforms and seals around nails and staples with less buildup under siding. Proprietary design will not liquefy, bleed, or melt in contact with most building sealants or in extreme summer temperatures.

Engineered for handling ease and performance reliability

- Fast-convenient application
 - Split-liner for easy and accurate positioning of tape, especially long lengths
 - Bonds to most common building materials without primers and staples even at temperatures as low as -18°C or as high as 49°C
 - No adhesive melting or staining in the summer heat
- High tack to grab fast and tight even on damp surfaces
- Innovative, thin proprietary design reduces aggregate thickness around windows and doors while effectively sealing around nails and staples
- No adverse reaction with most building sealants (preliminary data for synthetic rubber, butyl, polyurethane, silicone and silane terminated hybrids)
- Resists UV exposure for up to 3 months
- BRANZ appraised #775 (2012)
- Passes nail sealability before and after thermal cycling
- Meets AAMA 711-05
- Approved by the International Code Council Division 07. Evaluation ESR-2797



3M™ All Weather Flashing Tape 8067

Test Description	Tape Thickness (Backing & Adhesive)	Adhesion to Housewrap*	Adhesion to Polyethylene	Adhesion to OSB	Nail Sealability before and after Thermal Cycling	Adhesion to Anodized Aluminum after 7 days at 80°C	Adhesion to Anodized Aluminum after 7 days in water	Adhesion to Anodized Aluminum after Thermal Cycling	Adhesion to Anodized Aluminum after UV Exposure	Application Temperature Range °C	Service Temperature Range °C
Test Method	ASTM 3652	ASTM D-3330 per AAMA 711-05	ASTM D-3330 per AAMA 711-05	ASTM D-3330 per AAMA 711-05	ASTM E331 as modified per AAMA 711-05 Annex 1	ASTM D3330 after conditioning per AAMA 711-05	ASTM D3330 after conditioning per AAMA 711-05	ASTM D3330 after conditioning per AAMA 711-05	ASTM D3330 after conditioning per AAMA 711-05	ASTM D3330	Tested per AAMA 711-05
Results	0.25mm	55N/100mm	66N/100mm	66N/100mm	Pass	77N/100mm	71N/100mm	82N/100mm	66N/100mm	-18 to 49°C	-40 to 80°C

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.

* Spun bonded polyethylene



3M™ All Weather Flashing Tape 8067 is available in the following roll sizes:

- 76.2mm x 22.8m
- 152mm x 22.8m

Additional widths may be available on request

3M™ recommends the use of the 3M™ 540 Polyurethane Sealant or 3M™ 755 Hybrid Sealant, for a good bond to the flashing tape backing.

To learn more, see our video:

www.youtube.com/watch?v=zHLgCT_E37Y

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.



3M New Zealand Limited

94 Apollo Drive, Albany
Auckland, New Zealand
Phone: 0800 474 787
Fax: 0800 508 980
Email: 3mznzib@mmm.com
www.3m.com/adhesives

3M Australia Pty Limited

Building A, 1 Rivett Road
North Ryde, NSW 2113
Australia
Phone: 136 136

www.3m.com.au

3M is a Trademark of the 3M Company.

© 3M 2012. All Rights Reserved. Please Recycle