## 3M™ Extreme Sealing Tapes @<sub>292</sub>




## From Trailer, Bus and Rail Car Roof Seams to Metal Enclosures, a Sure Winner **Over Traditional Sealants**

- Sticks on contact to many metals and plastics without dripping, oozing or clean-up
- Increases productivity throughput with no drying time; immediately paintable\*
- Conforms over contours, edges, rivets and screw heads for a water tight seal
- Looks neat and precise for improved aesthetics
- Outstanding resistance to many common industrial solvents
- Excellent resistance to abrasion and high pressure washing

<sup>\*</sup>Accepts many paints. Test paint on tape to check for compatibility.





## Suggested Uses

- RV trailer and roofs
- Metal enclosures
- Awnings
- Trailer home roofs
- Metal storage buildings
- Vent stacks/windows
- Gutters and downspouts
- Skylights
- Outdoor signs/displays
- Leak patching and repairs



## Scan the code to download the 3M™ Extreme Sealing Tape Exterior **Durability Report.**

			Tape	Tensile Strength	90° Peel Adhesion Strength† lb/in (N/cm)							
Product	Color	Backing/ Adhesive	Thickness mils (mm)	lb/in (N/cm)	Aluminum	Stainless Steel	Glass	Truck Paint	PVC	ABS	Widths in (mm)	Length yd (m)
4411G	Grey	lonomer Film/Pressure Sensitive Acrylic	40 (1)	. 13 (23)	15 (26)	16 (28)	15 (26)	15 (26)	15 (26)	16 (28)	0.75, 1, 2, 25, 3, 4 (19, 25, 50, 65, 75, 100)	36 (32.9)
4411N	Neutral/Translucent		40 (1)		15 (26)	15 (26)	15 (26)	14 (25)	16 (28)	16 (28)		36 (32.9)
4411B	Black		40 (1)		19 (33)	17 (30)	19 (33)	17 (30)	19 (33)	18 (32)		36 (32,9)
4412N	Neutral/Translucent		80 (2)		18 (32)	18 (32)	19 (33)	19 (33)	19 (33)	19 (33)		18 (16.5)

<sup>†</sup>Adhesion promoters were used on peel Adhesion test substrates.