

# PRODUCT DATA SHEET



## 165 DOUBLE SIDED TAPE

Double Sided Adhesive Coated Polyester

### Product Features:

- Excellent plasticiser migration resistance.
- Offers a secure bond under high temperatures.
- Good resistance to solvents, chemicals, UV and heat.
- Exceptional bonding performance to low surface energy products.
- Used to mount ABS plastic plates in Automotive industry.
- Laminating and mounting of EPDM and rubber materials.
- Also used to fix decorative trim in furniture industry.

### Product Specifications:

- **Adhesive:** Solvent Based Acrylic Adhesive
- **Carrier:** PET
- **Total Thickness:** 0.20mm
- **Liner:** Transparent Polyolefin Film
- **Colour:** Transparent
- **Peel Adhesion:** 2kg per 25mm
- **Temperature Resistance:** -20 to 180 Degrees Celsius

All information and recommendations issued on **HUSKY TAPE CONVERTING** products, has been based on research and is believed to be reliable, but does not constitute a warranty. **All HUSKY TAPE CONVERTING** products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.

**MP170703**



**Adept**

**Industrial**

**Solutions**

**Pty Limited**

Telephone: 1800 008 590  
sales@adept-industrial.com.au  
www.adept-industrial.com.au