



Adept
Industrial
Solutions
Pty Limited

3M™ Hot-Melt Applicator and Adhesives



Fast setting adhesives.
Applied for speed and
durability.



3M Hot Melt Applicator

The next generation of 3M Hot Melt Applicators for our TC/TC-Q Adhesives is here!

The comfortable, efficient design of our new 3M Hot Melt Applicator TC/TC-Q combines our previous TC and Quadrack models while still offering regular and low-temperature versions to ensure you can utilise our various adhesives. This new applicator delivers high quality and cost efficiency with a new and improved lightweight, economic design.

Improved features include a new soft-feel handle for more comfortable use. The updated design also incorporates a new heater housing that heats the glue more evenly before feeding it straight through the gun, resulting in a smoother application.



Heats up fast and even easier to use.

- Heats in just 6 minutes from room temperature.
- Adjustable trigger for different outputs per trigger pull, or to suit different hand sizes.
- Narrow profile for better nozzle visibility to help with accuracy.
- Sturdy base keeps the tool upright when not in use so glue doesn't melt back.
- No Quadrack converter needed; easily interchange a Q or TC style hot melt adhesive stick.

Whether you are in Construction, Electronics, Furniture, General Industrial, Signage, Specialty Vehicle, Transportation or Woodworking, there is a 3M Hot Melt Adhesive to suit your application.

3M Scotch-Weld Adhesives to suit the new Hot Melt Applicator TC/TC-Q

The 3M Hot Melt Adhesive system are fast setting adhesives, applied for speed and durability.



TCQ 3738 - Tan 5kg:
High delivery rate and long bonding range. General purpose for wood, plastic and furniture.



TCQ 3764 - Clear 5kg:
Flexible at low temperatures. Can bond many plastics and polyolefins. Good impact resistance.



TCQ 3762 - Tan 5kg:
Fast setting for corrugated packaging, recoupage etc. Low cost, general purpose.



LTQ 3792LM - Clear 5kg:
Low Melt. Long bonding range. General purpose for heat sensitive substrates, eg. POS displays.



LTQ 3762LM - Light Amber 5kg:
Low Melt version of 3762. Fast setting for packing applications, beadboard, corrugated and displays.

Converting

Converting to die cutting can add value to any product by increasing design flexibility and freeing designers from many constraints, resulting in higher quality finished products.



Safety First!

Do you have the right safety PPE for your employees? When involved with industrial abrasives or aerosol spray adhesives and cleaners, safety glasses or goggles, as well as a respirator may be the workplace safety you need.



To learn more about how Adept Industrial Solutions can assist your business with the right product for your application, contact Kieran or Adel at Adept Industrial Solutions on 1800 008 590.

**Adept
Industrial
Solutions
Pty Limited**

Freecall: 1800 008 590
www.adept-industrial.com.au
sales@adept-industrial.com.au

Please note that the technical information and data provided within should be considered representative or typical only and should not be used for specification purposes. User should evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of application.